

# Триггер InvoiceStatusTrigger

## Изменение статуса счёта после выполнения всех его услуг

 **TMMIS-3333** - Проект Jira не существует, либо недостаточно прав на его просмотр.



После включения настройки "Платные услуги: Аванс", необходимо также провести на БД триггер [Администрирование. Триггер. \(TMMIS-3333\). Изменение статуса счёта после выполнения всех его услуг. sql](#), изменив в нём дату проверки счетов на дату включения настройки.

### SQL-код триггера

```
declare @scriptGuid uniqueidentifier,
        @taskNumber varchar(10),
        @scriptName varchar(150),
        @scriptdescription varchar(max)

set @scriptGuid = 'A7681C28-A62D-4E78-B258-3AE919ECD83B' --
set @taskNumber = 'TMMIS-3333' -- Jira
set @scriptName = '. . (TMMIS-3333). ' -- ( )
set @scriptdescription = '. . (TMMIS-3333). ' --

if (not exists(select 1 from web_script where [guid] = @scriptGuid))
begin
    insert into web_script(x_edition, x_status, [guid], taskNumber, Name, [description], RunCount, Success)
    select 1, 1, @scriptGuid, @taskNumber, @scriptName, @scriptdescription, 1, 0
end
else
begin
    update web_script
    set RunCount = RunCount + 1
    where [guid] = @scriptGuid
end

/* ----- end of: ----- */
if exists (select 1 from sys.objects where name = 'InvoiceStatusTrigger' and type = 'TR')
begin
    drop trigger [dbo].InvoiceStatusTrigger
end

go

create trigger [dbo].InvoiceStatusTrigger on hlt_SMTAP after insert
as begin
    if (((select max(rf_InvoiceID) from inserted) = 0) or ((select isnull((select top 1 ValueInt
from x_UserSettings where Property = ' : ' and rf_UserID = 1), 0)) = 0))
        return

    declare @doneStatusId int = (select isnull((select top 1 InvoiceStatusID from hlt_InvoiceStatus
where Code = '10'), 0)) --
    declare @ofdStatusId int = (select isnull((select top 1 InvoiceStatusID from hlt_InvoiceStatus
where Code = '9'), 0)) --

    update invoice
    set rf_InvoiceStatusID = (
        select case when count(smt.SMTAPID) >= count(bs.BillServiceId)
        then case when (select isnull((select top 1 ValueInt from x_UserSettings where
Property = ' 1' and rf_UserID = 1), 0)) > 0
            then @ofdStatusId
```

```

else @doneStatusId end
else invoice.rf_InvoiceStatusID end
from hlt_Invoice inv
join hlt_InvoiceStatus status on inv.rf_InvoiceStatusID = status.
InvoiceStatusID and status.Code = '3' --
left join hlt_BillService bs on bs.rf_InvoiceID = inv.InvoiceID
left join hlt_SMTAP smt on smt.rf_InvoiceID = inv.InvoiceID and smt.
rf_BillServiceID = bs.BillServiceID
where inv.InvoiceID = invoice.InvoiceID
)
from hlt_Invoice invoice
join hlt_InvoiceStatus status on invoice.rf_InvoiceStatusID = status.InvoiceStatusID and status.
Code = '3' --
where invoice.InvoiceID in (select distinct rf_InvoiceID from inserted) and invoice.Date >=
'2023-08-21T00:00:00'
end

go

/* ----- */

update web_script
set Success = 1
where [guid] = 'A7681C28-A62D-4E78-B258-3AE919ECD83B'

/* ----- end of: ----- */

```

В строке 54 скрипта, указанного выше необходимо заменить дату

where invoice.InvoiceID in (select distinct rf\_InvoiceID from inserted) and invoice.Date >= **'2023-08-21T00:00:00'**